

504011

MONTOSPRAY


MONTÓ
profesional

Date of Registration

13-08-2021 ANTI-SLIP

Version

4 08/19/2024



TYPE

E-MAIL

LINE

MULTISURFACE SPRAY

DESCRIPTION

Transparent spray based on modified acrylic varnish, with anti-slip particles and a matte finish. Improves adhesion and reduces the risk of slipping on damp or wet surfaces.

USE

Exterior/Interior

Metal

Wood

Asphalt fabric

Glass and ceramic tiles (perform a prior adhesion test)

Granite

PVC and plastic (perform a prior adhesion test)

property

Mat

Wash-resistant

Quick and easy application

Quick drying

Transparent

Adhesion on a wide range of surfaces

TECHNICAL SPECIFICATIONS

Reference color ANTI-SLIP MONTOSPRAY

Approximate yield per layer Depending on the use of the product

Dry to the touch 30min

Drying for reapplication 1-2 hours

Color Transparent

SURFACE PREPARATION

New surfaces

New wood:

The surface must be free of foreign products and/or residues.

Apply to wood with a moisture content of less than 12%.

Apply to healthy, well-degreased, dust-free and dry wood.

Sand and remove any adhesive residue from joints and processing defects.

If the wood shows signs of aging, it must be sanded beforehand and the resulting dust must be removed by brushing or other mechanical means.

Protect areas you don't want to paint.

Generally, remove products that are poorly adhering or in a damaged condition.

Iron, derivative metals and other metals

The surface must be free of foreign products and/or residues.

The surface must be degreased, clean and dry.

On rusty surfaces, rust must be removed by the usual methods recommended by Montó, using a rust inhibitor manufactured by our company, which must be applied beforehand.

Protect areas you don't want to paint.

Generally, remove products that are poorly adhering or in a damaged condition.

504011

MONTOSPRAY

Date of Registration

13-08-2021 ANTI-SLIP

Version

4 - 19/08/2024


MONTÓ
profesional

Works (plaster, cement and derivatives, cardboard): Remove foreign products and/or residues.
 The surface must be degreased, clean and dry. Remove any efflorescence using traditional methods. Generally remove poorly adhering or damaged products.

Restoration and**maintenance Varnished**

or painted wood: Always check the adhesion of previous varnish or paint and, if in doubt, remove it.

If in doubt, remove any previous varnish or paint.

If silicone-based cleaning products were used during maintenance, it is recommended to polish the wood until they are completely removed.

Enamelled iron and derivatives:

1. On paints in good condition, sand to open the pores, checking that the adhesion is perfect.
2. On damaged paints, remove them by mechanical or chemical methods and treat the surface as a new one.

HOW TO USE**Application notes**

Shake the container vigorously for approximately 2 minutes to perfectly homogenize the contents.

Perform application tests in a less visible area.

Protect areas that are not to be painted.

Apply from a distance of 25-30 cm from the surface, in light, crisscross layers.

Do not apply the product at high temperatures or on surfaces exposed to strong sunlight.

Ensure good ventilation during drying.

Do not apply if relative humidity exceeds 80%.

Do not use at temperatures below 15°C.

When finished, empty the contents of the spray nozzle with the container turned upside down.

Approximate yield per 400 ml container: 1.2 - 1.6 m² (two cross-layers).

Do not walk on the surface for 24 hours after application.

Solvent for dilution and cleaning

Solvent 1406-05**How to use****Approximate dilution****System****Procedures depending on the type of surface**

Primer	Intermediate	Finish
construction		
MAX Montospray Anti-Slip		Anti-slip Montospray
STD		Anti-slip Montospray
Metal		
MAX Montospray Anti-Slip		Anti-slip Montospray
STD		Anti-slip Montospray
Wood		
MAX Montospray Anti-Slip		Anti-slip Montospray
STD		Anti-slip Montospray

SECURITY

504011

MONTOSPRAY

Date of Registration

13-08-2021 ANTI-SLIP

Version

4 08/19/2024

MONTÓ
profesional

Do not eat, drink or smoke during application. In case of contact with eyes, rinse thoroughly with clean water. Keep out of reach of children. Do not empty into drains. Store in a dry place, protected from the weather, at a temperature between 5 and 35°C. For further information, see the product safety data sheet.

NOTE

Maximum recommended storage time: 48 months from manufacture, in original, perfectly closed packaging, stored indoors, at 35°C.
temperature CONTAINED between 5°C and

The information presented here is based on our current knowledge, laboratory tests and practical use under specific conditions. Since it is impossible to establish an adequate description for every type and condition of the supports to be painted, we cannot guarantee absolute reproduction in the specific.

PACKAGING

0.4L